



STAX 140W

STAX140WB5K

SAP CODE: 2001653



Photometric Diagram



Unit: cd

- C0/180 110.0deg
- C90/270 110.0deg

140W LED floodlight

An efficient and stylish LED floodlight for general area lighting.

KEY INFORMATION

Lumen Output	18410lm
Input Power	140W
Hole Cutout Size	N/A
Install	SURFACE MOUNT
Dimming Options	Non-Dimmable
Trim Colour	BLACK
Warranty	3yr
IP Rating	IP65
IK Rating	IK08
IC Rating	N/A
Rebate Scheme Approvals	REPS; IPART 132.29

PHOTOMETRIC

Efficacy	132lm/W
LED	SMD
CCT	5000K
CRI	>70
Beam Angle	110°

ELECTRICAL

Driver	Integral
Supply Input	220-240V, 50/60Hz
Driver Output Voltage	120VDC
Power Factor	>0.9
LED Input Current (nominal)	1200mA
Useful life @Ta25° (L70)	50,000hr

CONSTRUCTION

Housing	Aluminium ADC12
Optics	Polycarbonate Diffuser
Adjustable Angle	0-180°
Fixings/Hardware	Bracket
Connection Type	1m Flex
Total Weight	2.8kg
Dimensions	368 x 300 x 53mm
Operating Ambient Temp.	-20 to 50°C
Electrical Classification	Class 1