SPECIFICATION SHEET



Uni Series Tri-Colour LED Batten

Emerald Planet's Uni Series Tri-Colour LED Batten features switch controlled colour temperature, giving you the flexibility to match existing lighting colours.



FEATURES AND BENEFITS

- Switchable tri-colour 4,000K, 5,000K, 6,000K.
- Traditional batten profile.
- Surface mountable or suspendable.
- Flicker free driver.
- No external junction box required.
- Broad 120° beam angle.
- IP65 models available.
- Also available with built-in motion sensors and emergency models

SPECIFICATIONS

Model	EP-UNI- T620-18	EP-UNI- T1220-25	EP-UNI- T1220-35	EP-UNI- T1220-45	EP-UNI- T665-18	EP-UNI- T1265-25	EP-UNI- T1265-35
Length	600mm	1,200mm	1,200mm	1,200mm	1,200mm	1,200mm	1,200mm
Power consumption	18W	25W	35W	45W	18W	25W	35W
Output	2,160 lm	3,000 lm	4,200 lm	5,400 lm	2,160 lm	3,000 lm	4,200 lm
Efficiency	120 lm/W						
Colour temperature	4,000K, 5,000K, 6,000K						
CRI	>80						
Beam angle	120°						
IP rating	IP20 or IP65						
Lifetime rating	>60,000 hours						
Warranty	Five years						
Source	Stock	Stock	Stock	MTO	Stock	Stock	MTO

INDUSTRIES



Retail, hospitality, commercial offices, education, and industrial.

OLD LIGHT TECHNOLOGIES



shine-on.com.au | 1300 013 648 | info@shine-on.com.au (109, 63-85 Turner Street, Port Melbourne Victoria 3207 | 17a Kangaroo Avenue, Eastern Creek NSW 2766

