

- Corrosion proof, good vandal resistance for general circulation areas.



*Sensor versions available on request (subject to MOQ)

FEATURES

- Polycarbonate body
- Built-in high efficiency SMD chips
- Constant current driver fitted
- Opal polycarbonate diffuser
- IP65 weatherproof and IK10 vandal-proof
- Large 6mm terminal block for easy installation
- Emergency option available in page 71
- Fitting colour: White

INCLUDES

- LED bunker with driver
- Mounting accessories

INSTALLATION OPTIONS

- Surface mounted

APPLICATIONS

- Walkways
- Hallways
- Balconies
- Industrial
- Commercial

WARRANTY

- Five years (subject to terms and conditions)

CERTIFICATION	IP RATING	DIMMABLE	Ra	DISTRIBUTION	DIMENSIONS(mm)	IK RATING
			Ra≥80		 8W: Ø27.5, 98 13W: Ø32.7, 113	IK10 5kg at 405mm

Part No.	Voltage	Watt.	PF	Color Temp.	Lumens	Beam Angle	Lifetime L70B50	Net Weight (kg)
282001	100-240V	8W	0.9	3000K	700lm	110°	50000h	0.74
282002	100-240V	8W	0.9	4000K	750lm	110°	50000h	0.74
282003	100-240V	8W	0.9	5000K	750lm	110°	50000h	0.74
282004	100-240V	13W	0.9	3000K	1100lm	110°	50000h	0.91
282005	100-240V	13W	0.9	4000K	1200lm	110°	50000h	0.91
282006	100-240V	13W	0.9	5000K	1200lm	110°	50000h	0.91

Part No.	Model No.	VEET Status	IPART Status
282001 282002 282003	YKBHEB1-8W	Approved No.: 4454	Approved No.: 24143S13-DHEJGJGG
282004 282005 282006	YKBHEB1-13W	Approved No.: 4454	Approved No.: 24143S13-DHEJGJGG

[1] Operating Frequency=50/60Hz;

[2] Operating Temperature:-30 °C~+50 °C

