

## LED Sensor Panel Series 2

### SPECIFICATIONS

VOLTAGE	220-240AC
POWER FACTOR	>0.90
CRI	>80
IP RATING	IP20
BEAM ANGLE	110°
INSTALL ACCESSORIES	Surface Mount Kit Recessed Frame Suspension Kit

#### Occupancy and Daylight built in Sensor:

MOUNTING HEIGHT	3.5m
DETECTION RANGE	8m Diameter
DAYLIGHT THRESHOLD	450 Lux
MOTION HOLD	20mins
STANDBY	30% dim
ACCESSORIES	Remote Control



### ILUMINOUS MODELS

MODEL	POWER	LCP	LUMEN	DIMENSIONS	CCT
PPAN18W3X123KDS	18w	17.4w	2340	295*1195*30mm	3000K
PPAN18W3X124KDS					4000K
PPAN18W3X125KDS					5000K
PPAN18W3X126KDS					6000K
PPAN25W3X123KDS	25w	24.68w	3250	295*1195*30mm	3000K
PPAN25W3X124KDS					4000K
PPAN25W3X125KDS					5000K
PPAN25W3X126KDS					6000K
PPAN20W6X63KDS	20w	19.78w	2600	595*595*30mm	3000K
PPAN20W6X64KDS					4000K
PPAN20W6X65KDS					5000K
PPAN20W6X66KDS					6000K
PPAN25W6X63KDS	25w	24.5w	3250	595*595*30mm	3000K
PPAN25W6X64KDS					4000K
PPAN25W6X65KDS					5000K
PPAN25W6X66KDS					6000K

### GET IN TOUCH

 [info@primsal.com](mailto:info@primsal.com)

 [primsal.com](http://primsal.com)