

Plexis Series

Mark II Recessed Circular

Designed for flexibility and function, our Plexis Series of LED circular fittings offers a solidly-constructed, high performing luminaire that will deliver exceptional return on investment for any retrofit application.



FEATURES AND BENEFITS

- **New generation high efficiency.** 2835 LED chips.
- **Super high-efficiency Japanese light guide plate.** >95% throughput produces high output even light distribution.
- **Premium double stage PFC, non flicker.** Constant current driver maximises LED efficiency and lifetime.
- **Anti glare, non reflective materials.** Provides even light for reduced eye strain.
- **Separate lamp and driver for easy installation.** With unique pop lock design for ultra secure connection.
- **Latest technology aluminium heat dissipation system.** With thermal cavity.
- **Slim and compact.** Flush mounted modern design.
- **Dimmable option available.**
- **Five year warranty.**

SPECIFICATIONS

Model	CPL-M2-15W-185-xx	CPL-M2-18W-225-xx
Power consumption	15.5W	18.3W
Output	1,200 lm	1,440 lm
Colour Temperature	4,000K, 6,000K	3,000, 4,000K
Efficiency	80 lm/W	80 lm/W
Diameter	199mm	240mm
Cutout	180mm	223mm
CRI	≥80	
Beam angle	120°	
Lifetime rating	35,000 hours	
Warranty	Five years	
Source	Stock	

INDUSTRIES



Retail, office, education, accommodation, and industrial.

OLD LIGHT TECHNOLOGIES



Fluorescent, metal halide type 2 and incandescent.

PRODUCT DETAIL



Aluminium heat dissipation system with thermal cavity

Unique pop lock design for ultra secure connection.

Premium double-stage PFC, non flicker.

Separate lamp and driver

