

- Only 23mm thick. Easy installation.



FEATURES

- Three selectable colour temperatures
- Surface mounted oyster light
- High efficiency SMD chips
- Polycarbonate base
- Ultrathin body
- Edge lit
- Opal diffuser
- Low profile

DIMMING OPTIONS

- Trailing and Leading Edge
- Universal

INCLUDES

- Internal dimmable constant current driver
- Mounting accessories

APPLICATIONS

- Residential
- Hallways
- Stairwells
- Porches
- Walls & ceilings
- Aged care
- Bathrooms

WARRANTY

- Five years (subject to terms and conditions)

| CERTIFICATION | IP RATING | TRI-COLOUR | DIMMABLE | Ra | DISTRIBUTION | DIMENSIONS(mm) |
|---------------|-----------|------------|-------------------------------|-----------|--------------|----------------|
| | | | leading and trailing edge | Ra≥80 | | |

| Order Code | Part No. | Model No. | Voltage | Watt. | PF | Color Temp. | Lumens | Beam Angle | Lifetime L70B50 | Net Weight (kg) |
|------------|----------|-------------------|----------|-------|-----|-----------------|------------------|------------|-----------------|-----------------|
| 181005 | 181005 | CLE1P2T-SCD-D3017 | 220-240V | 17W | 0.9 | 3000/4000/5000K | 1550/1700/1700Lm | 120° | 50000h | 0.71 |
| 181006 | 181006 | CLE1P2T-SCD-D4324 | 220-240V | 24W | 0.9 | 3000/4000/5000K | 2150/2400/2400Lm | 120° | 50000h | 1.30 |

[1] Operating Frequency=50/60Hz;

[2] Operating Temperature:-20 °C~+40 °C

